

Using the New 3M SPP Pad:



Scotch-Brite™ Surface Preparation Pads (SPP)



- Eliminates the use of chemical strippers
 - Use 3M™ Neutral Cleaner or water
 - Reduces labor and material costs
 - Effectively removes floor finish, leaving a clean surface ready for recoating
 - **Environmentally preferred** cleaning method
1. SPP pads are ¼” thick so always use a “**backer**” pad (Blue, Red) on the floor machine to assure good contact to the floor and stripping conformability to an uneven floor surface.
 2. This pad is designed to **remove 2-4 coats of floor finish**, so it is an excellent way to either DEEP SCRUB or potentially STRIP a floor of finish much faster and without harsh chemicals.
 3. **Using on a single disk floor machine** – dust mop floor with **Easy Trap Duster**, put down plenty of #3 Neutral Cleaner on the floor (DO NOT USE STRONG CHEMICALS OR STRIPPERS AS THE SOFTENED FINISH WILL QUICKLY “LOAD” THE PAD). Scrub surface twice with the pad alternating direction if possible. Change pad often (generally every 500-1000 sq. ft) as pad is very dense and loads quickly). Wet vac up solution.
 4. **Using an Autoscrubber** – Dust mop floor with Easy Trap. Use “backer” pad with SPP pad and dispense plenty of 3# neutral cleaner on floor as you scrub with the machine going over floor **twice** (you can also do a double scrub process with the first pass scrubbing and second pass scrubbing and picking up solution). Try to scrub in both directions to assure getting into low spots. Use single disc if needed for edges/corners or tough areas.
 5. **Rinse floor very well with flood rinse and water.**
 6. Let dry completely, test for any residue on the floor (run hand across the floor to check for white powder residue).
 7. Lay the new 3M floor finishes for a beautifully finished result.

Key Points:

- SPP pad effective life is about 4,000 – 5,000 sq. ft.
- Use plenty of neutral cleaner to “help “flush” residue form the pad and change pad often to assure good aggressiveness in removing floor finish.
- Rinse pads well after use to remove residue.
- Customer will see significant cost savings vs. conventional stripping/scrubbing processes and a BEAUTIFUL FLOOR after only 1-2 coats of the new 3M finishes.